

Air mover AirMaxx 2000-H

Technology / Employment

- Connection ready air mover for set up in a room for optimal air circulation.
- Strong radial fan built into durable, handy stainless steel housing.
- Hose connectors for 3 x hose D = 100 mm or 6 x hose D = 50 mm.
- With inserted heater (optionally switchable).



Application & functioning

Area of use

Drying acceleration by increase of the air circulation after damages caused by water, in the building drying process, after carpet cleaning. Also for chilling and ventilating.

With inserted heater (optionally switchable)

Dimensions & installation

Installation / mobility

Plastic feet on the bottom and laterally for upright or horizontal set up on the floor or other flat undergrounds. Easy to carry by handle, slim dimensions.

Initiation

Plug into the socket. Switch on at on/off-switch. Switch on the heater if necessary.

Air inlet / air outlet

Air inlet over air filter at the lower surface, air outlet over three connecting pieces D = 100 mm or six connecting pieces D = 50 mm. (Has to be indicated with the order)

Maintenance

Change air filter. Outside and inside cleaning

Dimensions

Height / width / depth:
225 mm / 440 mm / 410 mm

Weight

12 kg

Technical data

Casing

Durably made of high-grade steel, hose connecting plate made of steel sheet flux coated. To dismantle simply. Cable keeping.

Air volume

2.000 cbm/h

Motor turns

2.350 U/min

Power consumption

280 Watts (without heater)

Power of heater (optionally switchable): 2.815 Watts *

Voltage

230 V / 50 Hz

Noise level

63 dB(A)

Conneting cable

aprox. 5 mtrs. with plug, cable keeping

Control elements

Switches for On/Off and heater On/Off

Guarantee

24 months from date of purchase

Optionally available accessories

Hoses